TATUNG

TATUNG V27MMBT

Rock the Details.....The Tatung 27"Widescreen LCD TV

Features

- •Comply Europe PAL/SECAM system, B/G, D/K, I, L/L'
- •Compatible with all 576i/576p/720p/1080i video formats
- •Universal video color system, PAL / SECAM / NTSC
- •Progressive Scan, 2:2 Pull Down
- •3D de-interlacer & Comb Filter
- •Auto Program System & Searching (APS)
- •Auto Volume & Power Control
- •Teletext, 255 pages

System Spec.

- •Resolution: 1366 x 768
- •Contrast Ratio: 1200:1
- •Response Time: 6.5 ms
- •Brightness: 400 cd/m2
- •HDMI connectivity

Items	Model Name	V27MMBT (EU Model)
Panel	Aspect Ratio	16:9
	Resolution	1366 x 768 (WXGA)
	Display Area (opening) H x V	596.259mm x 335.232 mm
	Pixel Pitch	0.4365 mm x 0.4365 mm
	Display colors	16,777,216 colors
	Contrast Ratio	1200:1 (typ.)
	Brightness (center)	400 cd / m2 (typ.)
	Viewing Angle (CR>10)	176° Hor. / 176° Ver. (typ.)
	Response Time (GTG)	6.5 ms (typ.)
TV function	Broadcasting System	PAL / SECAM
	Receiving Channel	B / G, D / K, I and L / L' (Multi-Europe)
	Sound System	NICAM / A2 (IGR)
	Resolution	Analog: 625i
	Data Broadcasting	Teletext 100 pages (FLOF /TOP) Auto Program Searching (APS)
Video Input	Video Color System	PAL / SECAM / NTSC
	AV1(SCART)	21-pin Scart (RGB / CVBS) x 1
	AV2 (SCART)	21-pin Scart (RGB / CVBS / SVHS) x 1
	AV3 (CVBS/ Y, C)	Composite (RCA jack) x 1
		S-Video x 1
	AV 4 (Component)	Y Pb Pr (720P / 1080i , HDTV ready) x 1
	AV 5 (HDMI)	HDMI 1.1 compatible; (Audio: two channel linear PCM 32,44.1 & 48Khz, 16, 20 & 24 bit)
PC Input (analog)	Signal Connection	D-Sub 15 pin
	PnP compatibility	DDC / 2B
	Scanning Frequency	f_H = 31.5 ~ 60KHz / f_V = 56 ~ 75Hz
Audio Input	Audio 1	Scart (build-in) x 2
	Audio 2	Composite/S-Video/ Component x 1
	Audio 3	PC x 1
Video Output	SCART 1	TV / CVBS/ S-Video
	SCART 2	TV / CVBS / S-Video
	CVBS	TV / CVBS / S-Video/SCART1/SCART2
Audio Out	Speaker (build-in)	10W +10W (rms) @ THD < 10% (7W + 7W @ THD < 1%)
	Headphone	Headphone Mini-jack (3.5Ø)
Feature	OSD Language	English, French , German , Spanish , Italian ,
		Finnish , Swedish, Dutch, Demark, Norway
	Function Keys	Power , Source , Menu , Up/Down(Channel) , +/-(Volume) , ASPECT
	Video Performance	3D Comb-filter , 3D De-interlace , Canal Plus , Teletext, Aspect Ratio Control (ARC)
		Auto Picture Control (APC), Video Enhance, Noise Reduction, PIP
	Audio Performance	Equalizer, Subwoofer, Auto Volume Control (AVC)
	Other Control	Sleep Timer, Auto Power On
Power	Power supply	AC 100V ~ 240V , 50 / 60Hz
	Power Consumption	< 160 W
Dimensions	W x H x D	841mm X 504mm X 272mm
Weight (Net)	Without Accessories	13.5 kg
Accessories	Remote Controller , Batteries , AC Power Cord	

**Product specification and design are subject to change without notice.